I'm not robot	reCAPTCHA
---------------	-----------

Continue

Clean the fluff filter under running water a page 4. Insufficient supply of air a Ensure that air can circulate. Ambient temperature greater than 35°C a Ventilate the room. The humidity in the room increases. Make sure the room is sufficiently ventilated. Exhaust air duct installed, the exhaust air routes directly into the open air? 7 kgHard-wearing fabrics, boil-proof fabrics made of cotton or linen.\*ISyntheticsmax. In this way, you can rest assured that the repair will be carried out by trained service technicians using original spare parts.12What to do if ....

[The door opens by itself. Dispose of them in an environmentally responsible manner. Emergency - Pull the mains plug out of the socket of them in an environmentally responsible manner. immediately or disconnect the fuse. Page 88Care and cleaning Dryer housing and control panel-Wipe clean with a soft, damp cloth. Do not clean with a water jet. Remove detergent and cleaning agent residue immediately. Exhaust air duct a Exhaust air duct installation instruction. Check the exhaust air duct as it may be clogged. cironed lightly ironed @cnot ironed cmangledPROGRAMMES TEXTILE TYPE AND INFORMATION\*LCottonsmax. 1.5 kgFabrics with membrane coating, water-repellent fabrics, functional clothing, fleece fabrics (dry jackets/trousers with membrane coating, water-repellent fabrics, functional clothing, fleece fabrics with membrane coating, water-repellent fabrics, functional clothing, fleece fabrics (dry jackets/trousers with membrane coating, water-repellent fabrics). items of laundry that have been worn for a short period of time.cShirts/Blousesmax. The appliance goes into the sleep mode after activating Finished in option apage 5.4p(Fluff filter/Exhaust air duct)indicator light flashes. Clean the fluff filter a page 4.Press the \$Start/Pause button to reset the displayed indication and then press the \$Start/Pause button again to restart the appliance if necessary. Exhaust air duct blocked or bent? Clean the exhaust air duct a page 8. If necessary, clean the insect screen on the exhaust air pipe. The programme has ended and allow to dry. CDelicates max. 2v Drying. Also suitable for subsequent drying. Environmental protection / Energy-saving tips- Before drying, spin the laundry in the washing machine a higher spin speeds minimise the drying time and reduce energy consumption. - Use the maximum recommended capacity, but do not exceed it a Programme overview, page 7.- Make sure the room is well ventilated during drying.- Clean the fluff filter after every drying cycle a Clean the fluff filter, page 4/11. Remove the laundry and switch off \$aSelected option activated/deactivated aindicator light on/off. See the separate Energy-saving mode instructions. a`H|]+E > y(3x + y) + E >a>((\$a(zyy³x x \$ V4&\u00fcu &\u00fcuProgrammes / FabricsDetailed overview of the programmes and fabrics aProgrammes and fabrics. ISynthetics Fabrics made from synthetic or blended fabrics. Dryness levels to select with the LCottons and ISynthetics programmes:+: Cupboard Dry Plus Thick and multi-layered fabrics.+. 8v Installation . 9v Optional accessories . a Do not use the +: Cupboard Dry Plus programme.- Starched laundry is not always suitable for dryers a starch leaves behind a coating that reduces the drying effect.- When washing laundry that is to be tumble dried afterwards, use the correct amount of fabric softener as specified in the manufacturer's instructions. For pre-dried, multi-layered fabrics or small, individual items of laundry, use the timed programme ends after the selected number of hours. Several minutes after activating Finished in option the display switches off to save energy. Can be turned in both directions.`Programme sequence H|]+- Æ-> Drying Timey Fine adjustChildproof lock(3x- xFinished inFluff filter/Exhaust air duct p V Low Heat 4 Wrinkle Guard Plus&Signal\$ Start/Pause(Further information can be found on page 5 The values may differ from the those specified depending on the type of fabric, mixture of laundry to be dried, residual moisture in the fabricand loading capacity. ® ÷Wool Finishmax. Automatic anti-crease function can be extended by up to 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. The standard setting for each programme is 60 min. \*Pryness levels can be selected individually a +: Cupboard Dry Plus, +. Th damp). Warm laundry feels damper than it really is. The selected programme does not suit the load. 10v Consumption rates . Turn the programme selector to Timed programme suitable for ironing after drying.\$÷Sportswear Functional clothing made of microfibre.ØTowels Terry-towelling laundry e.g. towels and bathrobes.1÷Mix A mixed load of fabrics made of cotton or linen fabrics that are still damp and easy-care fabrics.cSuper 40' Synthetics, cotton or blended fabrics.® ÷Wool Finish Woollen fabrics that are suitable for use in washers.cDelicates Lingerie made of synthetic fibres, cotton or blended fabrics. Octoon oct dryer is its low energy consumption. Every dryer which leaves our factory is carefully checked to ensure that it functions correctly and is in perfect condition. 1 kgLingerie made of synthetic fibres, cotton or blended fabric. Also for subsequent drying. Timed program coldmax. To activate/deactivate ((Childproof lock) start the programme or set the Finished in option and then press and hold the \$Start/Pause button for 5 seconds until a long acoustic signal is heard. aInstallation conditions a page 9.Exhaust air duct, page 1.qOne or more indicator lights are flashing. Clean the exhaust air duct a page 8.Switch off, allow to cool, switch back on, and restart the programme. (Power failure. The laundry is made drier. Should you have any questions, our after-sales service will be pleased to help. Environmentally responsible disposal Dispose of packaging in an environmentally-responsible manner. This appliance is designated according to European directive 2002/96/EC which governs waste electrical and electronic equipment (WEEE). This directive provides the framework for the EU-wide collection and reuse of used appliances. For further information about our products, accessories, spare parts and services, please visit: www.bosch-home.comIntended usePreparationv exclusively for domestic use, v only for drying fabrics which have been washed using water. Do not leave children unsupervised near the dryer. Keep pets away from the dryer. The dryer may be operated by children from 8 years of age, by persons who have limited physical, sensory or mental abilities and by persons who have inadequate experience or knowledge, provided they are supervised or have been instructed by a responsible person. Contents Pagev Preparation . Do not bend the exhaust air duct. Switch off the dryer and allow it to cool down. Remove the exhaust air duct. Remove the exha steel moisture sensors. Moisture sensors measure the moisture sensors. Open the door. 2. Clean the moisture sensors with a damp sponge which has a rough surface. Do not use steel wool or abrasive agents! Only when the appliance is switched off.9Installation- Scope of delivery: dryer, operating and installation instructions, basket for woollens (depending on the model).- Check the dryer for transport damage.- The dryer is very heavy. Cupboard Dry\* 1400 rpm (50%) 83 min 1.93 kWh1000 rpm (60%) 99 min 2.88 kWh800 rpm (70%) 116 min 3.58 kWhISynthetics 3.5 kg+. Do not attempt to lift it on your own.- Be careful to avoid sharp edges.- Do not set up in a room that is susceptible to frost. Freezing water may cause damage.- If in doubt, have the appliance connected by a specialist. Setting up the dryer. The mains plug must always be accessible. - Ensure that the appliance is placed on a clean, level and firm surface. - Install the exhaust air duct installation instruction. - Keep the area around the dryer clean. - Level the dryer using the threaded feetand a spirit level. Never remove the threaded feet! For mains connection, see Safety instructions a page 13.- Connect to an AC earthed socket. This is shown by jumps in the remaining time programmes, can be selected from min. 5v Notes on laundry. Make sure the dryer is level. After-sales service If you cannot rectify the fault yourself (e.g. switching off/on) a What to do if..., page 11/12, please contact our after-sales service. Can be turned in both directions. H|]+ Æ > Setting the drying time available only for timed programmes. Fine adjustment of dryness level. (3x x Setting the programme end. p VLow-heat drying reduced temperature.4Wrinkle Guard Plus Extends the anti-crease function. & Buzzer on/off. \$ Starts, pauses and continues the programme; activates or deactivates o water jet.- Remove detergent and cleaning agent residue immediately. Exhaust air duct a Exhaust air duct as it may be clogged. In this way, you can rest assured that the repair will be carried out by trained service technicians using original spare parts. Page 4zpaaH|]+Æ >H|]+Æ a>((\$a(zyy³x x \$ fabrics. A clean fluff filter minimises energy consumption. Clean the fluff filter after each drying cycle:1. Cupboard Dry@Single-layered laundry.+: Cupboard Dry@Single-layered laundry with thick, multi-layered parts. \$\displayered\$ Environmental protection / Energy-saving tips- Before drying, spin the laundry in the washing machine a higher spin speeds minimise the drying time and reduce energy consumption.— Use the maximum recommended capacity, but do not exceed it a Programme overview, page 7.- Make sure the room is well ventilated during drying.— Clean the fluff filter after every drying cycle a Clean the fluff filter, page 4/11.Remove the laundry and switch off the dryer54Control panelFluff filterSelect\$Start/PauseDoorInstallation a page 9 and Exhaust air duct installationInstructions, the InstallationInstructions and the separate Energy-savingmode instructions before operating the dryer. Selected option activated/deactivated aindicator light on/off. See the separate Energy-saving mode instructions. Before using the dryer for the first timerun the drying cycle without any laundry a page 6. Programme selector for setting the programme selector. VLow HeatReduced temperature for delicate fabrics, e.g. polyacrylic, polyamide or elastane, with a longer drying time. 4Wrinkle Guard Plus After the programme finishes, the drum moves at regular intervals to prevent creases. 10v After-sales service any fluff from the door/around the door and pull out the fluff filter. Open the door or press the \$Start/Pauseübutton; the drying cycle is interrupted. 2. Add or remove laundry and close the door. 3. If required, select a new programme and additional functions. Cupboard Dry\* 800 rpm (40%) 47 min 1.32 kWh600 rpm (50%) 59 min 1.72 kWh\* Programme setting for testing in accordance with applicable standard DIN EN61121.\*\* The values may differ from those specified, depending on the type of fabric, composition of laundry to be dried, residual moisture in the fabric and the amount of laundry being loaded. What to do if ... Turn the programme selector to Off and remove the mains plug from the socket. The \$Start/Pause indicator light does not light up. Mains plug glugged in? Programme selected? Check the socket fuse. (The display panel light and indicator lights (depending on mode) go out and the \$Start/Pause indicator light flashes. Energy-saving mode is activated a see the separate Energy-saving mode instructions. help.Environmentally responsible disposalDispose of packaging in an environmentally-responsible manner. This appliance is designated according to European directive provides the framework for the EU-wide collection and reuse of used appliances. For further information about our products, accessories, spare parts and services, please visit: www.bosch-home.comIntended usePreparation Set and adjust theprogramme individually12Dryingo exclusively for domestic use, vonly for drying fabrics which have been washed using water. Do not leave children unsupervised near the dryer. Keep pets away from the dryer. The dryer may be operated by children from 8 years of age, by persons who have limited physical, sensory or mental abilities and by persons who have inadequate experience or knowledge, provided they are supervised or have been instructed by a responsible person. Drying Close the door 3 Contents Page value of value of the door 3 Contents Page value of va programmes. At the end of the programme, turn the programme, turn the programme, turn the programme. Always dry very small fabrics (e.g. baby socks) together with large items of laundry (e.g. towels). Close zips, hooks and eyelets, and button up covers. Tie cloth belts, apron strings, etc. This allows the heat to dissipate. The remaining time is updated after a few minutes. The drum and door may be hot! Notes on laundry ... Labelling of fabrics Follow the manufacturer's care instructions. hcSuitable for tumble dry.Do not tumble dry the following fabrics:- Non-breathable fabrics (e.g. rubber-coated).- Delicate materials (silk, curtains made from synthetic materials (silk, curtains made from synthetic material) a these may crease.- Oil-stained laundry.Before drying for the first time- Do not put any laundry in the machine. Creasing in fabrics is reduced. 3. The basket contained in the drawer can be used to carry the laundry. Technical dataDimensions (DxWxH) 60 x 60 x 85 cm (height adjustable) Weight approx. Can be turned in both directions. 'Programme sequence H|]+- Æ-> Drying Time Setting the drying time available only for timed programmes. Yeight approx. Can be turned in both directions. 'Programme sequence H|]+- Æ-> Drying Time Setting the drying time available only for timed programmes. Yeight approx. Can be turned in both directions.' Programme sequence H|]+- Æ-> Drying Time Setting the drying time available only for timed programmes. Yeight approx. Can be turned in both directions.' Programmes sequence H|]+- Æ-> Drying Time Setting the drying time available only for timed programmes. Yeight approx. Can be turned in both directions.' Programmes sequence H|]+- Æ-> Drying Time Setting the drying time available only for timed programmes. Yeight approx. Can be turned in both directions.' Programmes sequence H|]+- Æ-> Drying Time Setting the drying time available only for timed programmes. Yeight approx. Can be turned in both directions.' Programmes sequence H|]+- Æ-> Drying Time Setting the drying time available only for timed programmes. Yeight approx. Can be turned in both directions.' Programmes sequence H|]+- Æ-> Drying Time Setting the drying time available only for timed programmes. Yeight approx. Ye end. Fluff filter/Exhaust air duct p V Low Heat Low-heat drying reduced temperature. 4 Wrinkle Guard Plus Extends the anti-crease function. & Signal Buzzer on/off. \$ Start/Pause Starts, pauses and continues the programme; activates or deactivates or deactivates ((Childproof lock). Further information can be found on page 57 Programme overview see also page 6.Sort the laundry according to type of textile and fabric. \$Start/Pause button selected? We will always find an appropriate solution and avoid unnecessary visits by engineers. The contact details of your local after-sales service can be found in the enclosed after-sales service directory. GB 0844 8928979 (Calls from a BT landline will be charged at up to 3 pence per minute. If in doubt have the socket checked by a specialist. The mains voltage and the voltage shown on the rating plate (a page 10) must be the same. The connected load and necessary fuse protection are specified on the rating plate. The mains voltage and the voltage shown on the rating plate. filter a page 4/11or check the exhaust air duct a page 8.H|]+- Æ->(Programme progress in the next steps of the drying cycle:H Drying;|] Iron Dry;+Cupboard Dry;- Æ- Programme pause aif required;>Programme end.((Childproof lock)You can lock the dryer to prevent the functions you have set from being changed inadvertently. 10v Consumption rates. Hang up fabrics! ASuper 40'max. 13Never start the dryer if it is damaged! Inform your after-sales service! \$\sigma\$ up fabrics! ASuper 40'max. 13Never start the dryer if it is damaged! Inform your after-sales service! InstallationInstructions and the separate Energy-savingmode instructions before operating the dryer.aaProgramme and switching the appliance on/off. 2 kgLaundry made of synthetic fibres, cotton or blended fabrics (for example) that needs to be dried quickly. Other sounds are not influenced by this option.aLIL Delicate materials (silk, curtains made from synthetic material) a these may crease. Oil-stained laundry. Before drying for the first time Do not put any laundry in the machine. 3 kgWoollen fabrics suitable for washers. 3481739 München/DeutschlandWTA74201ILPage 53 4 Programme selector / OffzpaaH|]+Æ >H|]+Æ a>((\$a(zyy^3x x \$ V4&x & \u00curum \u00e4\u00e  $I++|$\div\emptyset1\div cc$ ®  $\div c$  Set and adjust the programme individually 12 Drying volume of the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! Inform your after-sales service! Inspect the dryer if it is damaged! I Fabrics are not dried completely. Door closed? Programme set? qProgramme terminates shortly after starting. Ambient temperature greater than 5°C? Is the appliance loaded with the laundry? Load too small for selected programme apage 6/7. Loaded laundry dry? qWater is leaking out. .3/4v Display panel and settings . 3:00 h, in 10-minute steps.yFine adjustThe dryness levels can be increased in three levels. Open the door. 3 kgMixed items of laundry made of cotton and synthetics (Mix). Timed program warmmax. Select the \$Start/Pause button. Select the \$start/Pause button. drying. After drying, laundry is to be ... 13Never start the dryer if it is damaged!Inform your after-sales service!Inspect the dryerSort the laundryRemove all items from pockets, especially cigarette lighters. The drum must be empty prior to loading. Make sure your hands are dry. Remove the fluff (sweep your hand over the fluff filter). capacity 7 kgConnection voltage 220-240 VConnected load 2200 WFuse protection 10 AAmbient temperature 5 - 35°CProduct numberInside of doorThe rating plate can be found on the back of the dryer.WTZ1130WTZ20410WMZ20500Consumption ratesFabrics/programmesResidual moisture in the fabrics after spinningDrying time\*\*Energyconsumption\*\*LCottons 7 kg+. Other sounds are not influenced by this option. Programmes and fabrics aProgramme overview, page 7. Observe the care instructions on the care instructions on the programmes and fabrics. ISynthetics aProgramme overview, page 7. Observe the care instructions on the care instructions of the care instruction select with the LCottons and ISynthetics programmes:+: Cupboard Dry Plus Thick and multi-layered fabrics.+: 3 kgPre-dried, multi-layered, sensitive fabrics made of acrylic fibres, or separate small items of laundry. Use another objects?. Laundry remains loose and fluffy. Clean the exhaust air duct at regular intervals, e.g. every six months. The option activated/deactivated drying time (remaining time) for the recommended load is displayed. Off peak 0.0088 € per minute.)Please provide the after-sales service the product number (E no.) and the production number (FD) of the appliance.\*depending on the modelTrust the expertise of the manufacturer. Contact us for assistance. 11v What to do if ... Be careful as the door, the drum and the laundry may be hot. (Condensation in the exhaust air duct too long? Hot steam may escape. Installation - Fasten down loose leads a Risk of tripping - Do not operate the dryer where there is a risk of frost. - The safety information in the separate installation instructions for the exhaust air duct must be observed without fail. Mainsconnection- Connect the dryer to an AC earthed socket according to specifications, as otherwise it cannot be guaranteed that the appliance is completely safe. The cable cross-section must be sufficient. Only use earth-leakage circuit breakers with the following symbol: - The mains plug and socket must be compatible. - Do not use multiple plugs/couplings and/or extension cables. - Do not touch or hold the mains plug with wet hands a Risk of electric shock. Operation - Only load the drum with items of laundry. Check what has been loaded before switching the dryer on. - Do not use the dryer a Risk of explosion. - Dust risk (e.g. coal dust or flour): do not use the dryera Risk of explosion. - Do not put laundry containing foamed material. Switch off the dryer a elastic material may be destroyed and the dryer once the programme has ended. Defect- Do not use the dryer if it is defective or if you suspect that it is. Repairs must only be carried out by the after-sales service.- Do not use the dryer with a faulty mains cable. 11/12v Safety instructions. 10v Technical data . 36 kgMax. Display panel and settings panel and settings panel (status indicators) p(Fluff filter a page 8.H]+- Æ->(Programmes equence) These indicators show the programme progress in the next steps of the drying cycle:H Drying;|] Iron Dry;+Cupboard Dry;- Æ- Programme end.((Childproof lock)You can lock the dryer to prevent the functions you have set from being changed inadvertently. 3481739 München/DeutschlandWTA74201ILPage 2 aaaaL+|I+q\$q\$aq aqpa\$aq\$qaq\$ay aa aqaaaqaaaaaaaaaDryeren Instruction manual Page 310Optional accessories (order from the after-sales service using the order number, according to model)Exhaust air duct set The exhaust air duct set depth to save space. together or use a laundry bag.- Do not over-dry easy-care laundry a risk of creasing. Allow laundry to finish drying in the air.- Do not dry woollens in the dryer. The remaining time is updated after a few minutes. The drum and door may be hot! hc(c'c a V)caa \$aa O ÷ aa +aaaaRemove the laundry and switch off the dryer. panelFluff filterSelect\$Start/PauseDooraand Exhaust air duct installation instruction.aBefore using the dryer for the first timerun the drying cycle without any laundry a page 6.Programme or set the Finished in option and then press and hold the \$Start/Pause button for 5 seconds until a long acoustic signal is heard. Further information alnstallation instructions for exhaust air duct. 13Safety instructions for ex must NEVER...- be used for purposes other than those described above.- be modified in terms of its technology or attributes. Dangers- The dryer must not be used by children unsupervised near the dryer.- Keep pets away from the dryer.- Remove all objects from the pockets of garments. Pay particular attention to cigarette lighters a Risk of explosion - Do not lean or sit on the door with care. Remove the laundry from the dryer immediately and spread out. & Signal indicates program end if it is activated. 6 kgTerry-towelling laundry e.g. towels and bathrobes. 1 ÷ Mixmax. 2. Dispose of them in an environmentally responsible manner. Emergency- Pull the mains plug out of the socket immediately or disconnect the fuse. Dryeren Instruction manual Page 7aaaaL+|I+q\$q\$aqa12What to do if ... qThe door opens by itself. 3.5 kgNon-iron laundry made of synthetic fibres and mixed fabric, easy-care cotton. |Iron Dry c÷@c The condition of the laundry means it is suitable for ironing (iron clothes in order to avoid creases).+. Cupboard Dry\* 800 rpm (40%) 47 min 1.32 kWh600 rpm (50%) 59 min 1.72 kWh\* Programme setting for testing in accordance with applicable standard DIN EN61121.\*\* The values may differ from those specified, depending on the type of fabric, composition of laundry to be dried, residual moisture in the fabric and the amount of laundry being loaded.11What to do if ... Turn the programme selector to Off and remove the mains plug from the socket fuse. The display panel light and indicator lights (depending on model) go out and the \$Start/Pause indicator light flashes. Energy-saving mode is activated a see the separate Energy-saving mode is activated a see the separate Energy-saving mode is activated a see the separate Energy-saving mode is activated by a specialist. The mains voltage and the voltage shown on the rating plate (a page 10) must be the same. The connected load and necessary fuse protection are specified on the rating plate. 1. Take all accessory parts out of the drum. The drum must be empty. Clean and level. Do not install the dryer behind a door or sliding door which could prevent or obstruct the dryer door from opening. This will prevent children from locking themselves in and risking their lives. 2.10 Optional accessories (order from the after-sales service using the order number, according to model) Exhaust air duct set The exhaust air is extracted via a hose. Washer-dryer stack connection setThe dryer can be placed on top of a suitable washing machine with the same width and depth to save space. Cupboard Dry and Iron Dry (depending on the model). Degree of dryness can be finely adjusted; multi-layered textiles require a longer drying time than single-layered items of clothing. Recommendation: Dry separately. 9309 / 9000811321\*811321\*Robert Bosch Hausgeräte GmbHCarl-Wery-Str. While drying, the moisture sensors detect the actual load and correct the programme length. 0:20 h to max. In order to avoid danger, have the mains plug, then cut the mains cable off the appliance. Dispose of the appliance at a municipal waste disposal site. Packaging: Do not allow children access to items of packaging Risk of suffocation. All materials are environmentally friendly and reusable. Default = 0. Only grasp the plug body. Connect themains plugClean the fluff filterDo not operate the dryer without a fluff filter or with a defective fluff filter. Then press the \$Start/Pause button to activate the Finished in option. 3 kgCotton or linen fabrics that are still damp and easy-care fabrics. & "SignalFor switching the buzzer on and off. Provide adequate air circulation. Use y Fine adjust for the dryness levels a page 5. Fine layer of limescale on the humidity sensors a Clean the moisture sensors apage 8. Programme termination, e.g. mains power supply failure, door open or maximum drying time too long. Selectable values: 0, 1, 2, 3. After setting the level of the fine adjustment for a programme, it is also retained for other programmes, until y Fine adjust is changed again.3x- xFinished in The time when the programme has to end can be selected in one-hour steps, up to a maximum of 24 hours. If the fluff filter is very dirty or blocked, rinse with warm water and dry thoroughly.4. Insert the fluff filter so that you hear it engage.6End of the programme...Interrupt the programme1. Remove the fluff from the shaft of the fluff filter. They may, however, be refreshed in the dryera page 7, O÷Wool Finish programme (depending on model).- Do not iron laundry immediately after drying; fold items up and leave for a while a residual moisture will then be distributed evenly.- Knitted fabrics (e.g. T-shirts, jerseys) often shrink slightly the first time they are tumble-dried.

